



# Australia Pty Ltd

## MAINTENANCE SCHEDULE

Service Interval	Date Serviced	Kms Travelled	All Torque Nuts	Ride Height	Shock Absorber	Air Spring	Height Control Valve	Frame Hanger	Pivot Bush / Pivot Connection	S-Cam	Slack Adjuster	Caliper Guides & Bushes	Disc Brake Pads	Drum Brake Lining	Wheel Ends
------------------	---------------	---------------	-----------------	-------------	----------------	------------	----------------------	--------------	-------------------------------	-------	----------------	-------------------------	-----------------	-------------------	------------

### Year 1

30 Days / 5000 km			IC	I	I	I	I	I	I	I	I	I	I	I	I
3 Months			IC		I				I	LA	LA	I			LA
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

### Year 2

3 Months			IC		I				I	LA	LA	I			
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

### Year 3

3 Months			IC		I				I	LA	LA	I			
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

### Year 4

3 Months			IC		I				I	LA	LA	I			
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

### Year 5

3 Months			IC		I				I	LA	LA	I			
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

### Year 6

3 Months			IC		I				I	LA	LA	I			
6 Months			IC	I	IC	I	I	I	I	LA	LA	I	I	I	I
9 Months			IC		I				I	LA	LA	I			
12 Months			IC	I	IR	IR	IR	I	IR	LA	LA	IR	IR	IR	LA

NOTES: Preset wheel ends must be inspected every six months  
 Calipers should be inspected monthly for dust boot damage

KEY	
I	Inspect
IR	Inspect/Replace as Required
IC	Inspect/Check Torques
LA	Lubricate/Check Adjustment

Note: Maintenance intervals are for clean paved road conditions. For other road conditions intervals should be halved.